

# **PRODUCT DATASHEET**

## DOWNLIGHTS | SPOTLIGHTS-PAINTABLE PLASTER LIGHT

Downlights | Recessed mounted spotlight | 15w\*3 | Square shape Code# GC07008-15x3



## **Areas of Application**

- Shops
- Villa
- Hotel
- Club
- Corridors, stairways, entrance areas
- Galleries, museums residential interiors

#### **Product Features**

- Module structure, separate embedded installation, adapted to different LED light source and beam angles
- The height of the embedded parts can be adjusted
- Lamp can be adjusted the irradiation direction for precise lighting
- Deep hidden light source for anti glare
- Energy savings of up to 90% compared to halogen lamp spotlights
- High luminous efficacy, high CRI
- CCT optional and dimmable
- Die-cast aluminum housing, ensure excellent heat dissipation
- Uniform light output and good consistency, without flicker

## **Complete Product Data**

| Code#                      | GC07008-15x3       |  |
|----------------------------|--------------------|--|
| Wattage                    | 15W*3              |  |
| Installation Type          | Recessed           |  |
| Dimension                  | L220mm*W80mm*H50mm |  |
| Cutout                     | 225mm*85mm         |  |
| IP Rating                  | IP20               |  |
| Luminous Flux              | 1200lm*3           |  |
| Beam Angle                 | 15°, 24°, 36°      |  |
| <b>Working Temperature</b> | -25℃ ~55℃          |  |
| Certificates               | /                  |  |
| Warranty                   | 3 Years            |  |
| Packing Size               | /                  |  |
|                            |                    |  |

## **Driver Data**

| Driver Brand   | Tridonic, Osram, Philips, Lifud, Euchips, Eaglerise, etc. |
|----------------|---|
| Input Voltage  | 100-250VAC 50/60hz  |
| Output Voltage | 27-40Vdc  |
| Output Current | 350mA   |
| Power Factor   | >0.5 as standard; >0.9 optional                           |
| Efficiently    | 87% @230v   |
| IP Rating      | IP20  |
| Dimmable       | Non-Dimmable/Triac/0-10v/Dali Optional                    |
| Free Flicker   | Yes   |
| Certificates   | CE, CB, CCC, ENEC   |
| Warranty       | 3/5 Years   |
|                |   |

# Material&Housing Data

| Housing Color    | White  |
|------------------|--------|
| Reflector Color  | White  |
| Housing Material | Gypsum |

## **Photometric Data**

| LED chip brand    | Cree/ Osram /Bridgelux/ Epistar etc. |
|-------------------|--------------------------------------|
| Chip Type         | СОВ                                  |
| Color Temperature | 2700K, 3000K, 4000K, 5000K, 6000K    |
| CRI               | >80, >90                             |
| Life time         | >50000Hrs                            |
| Lumens efficacy   | 100-120lm/w                          |

#### **Dimensions&Installation**





PLEASE FIND A QUALIFIED ELECTRICIAN FOR INSTALLATION. Please read the instructions before you install and use the downlight.

- 1. Make sure the power is turned off in which you are installing the products.
- 2. Open the hole in the ceiling according to the lamp size. (Fig 1)
- 3. Put the embedded parts of lamps into back side, pay attention to pull the wire out. (Fig 2)
- 4. The self-tapping screw goes through the ceiling and locks the embedded wings of the lamp. (Fig 3)
- 5. Plaster the edge of embedded parts until the edge smooth with ceiling. (Fig 4)
- 6. Connect the light source module of the lamp to the mains supply and push it into the embedded parts. (Fig 5)
- 7. Restore power at the source and the installation is complete. (Fig 6)